

Industrial Stationary

AIR COMPRESSORS Jenny®



Base Plate Mounted Compressors

Standard Features

- Heavy-duty single or two stage cast iron compressor pump
Made in Somerset, PA USA
- Splash lubricated
- Belt driven with a large flywheel for extra cooling and easier start-up

- Each unit is filled with Jenny Ultimate Blue Compressor Pump Oil
- Directional air shroud for reduced pump temperatures
- Totally enclosed heavy-duty belt guard



Single Stage

Model	Pump	HP	Power Supply	125 PSI		
				Pump RPM	CFM Disp	Del'd Air
F12A-B	F	1/2	115 Volt (through 2 HP) or 230 Volt 1 Phase	680	3.4	2.2
F34A-B		3/4		1080	5.3	3.1
K1A-B		1		560	6.2	4.0
K15A-B	K	1-1/2	208, 230, 460 or 575 Volt 3 Phase	870	9.8	6.2
K2A-B		2		1140	13.1	8.0
GC2A-B	GC	3	208, 230, 460 or 575 Volt 3 Phase	480	13.1	9.1
GC3A-B				770	21.0	14.0
GC5A-B				1020	27.8	17.8
J5A-B	J	5		780	28.7	19.0

Electric

- Auto Start/Stop control with pressure unloader set at 105-125 PSI (single stage) or 145-175 PSI (two stage)
- Control group (not mounted)
- Check valve
- Magnetic starter is included on all 5 HP and larger units
- Industrial/Commercial grade UL Listed electric motor
- Thermal overload motor protection

Two Stage

Model	Pump	HP	Power Supply	175 PSI		
				Pump RPM	CFM Disp	Del'd Air
GT2B-B	GT	2	115 Volt (through 2 HP) or 230 Volt 1 Phase	450	9.1	7.1
GT3B-B		3		660	13.4	10.7
W3B-B	W	5	208, 230, 460 or 575 Volt 3 Phase	440	12.2	10.7
GT5B-B	GT			900	18.3	15.2
W5B-B	W	7-1/2	208, 230, 460 or 575 Volt 3 Phase Only	760	21.1	17.5
U75B-B	U			610	38.0	27.2
U10B-B		10	710	43.6	35.2	
T15B-B	T	15	208, 230, 460 or 575 Volt 3 Phase Only	520	72.4	56.5
T20B-B		20		670	92.6	72.2
T25B-B		25		780	107.0	83.0



Options

- Constant run control ■ Dual control
- Magnetic starter
- Oil sight glass
- Air line filter ■ Lubricator
- Aftercooler ■ Dryer
- Other pressures available upon request

Base Plate Mounted Compressors

- Powder coated, extra heavy steel base plate
- Large canister intake filter with replaceable filter elements
- Pressure relief safety valve
- Pressure gauge



K5HGA-B



T25KGB-B

Gas

- Constant run control set at 105-125 PSI (single stage) or 145-175 PSI (two stage)
- High quality pilot valve
- Pneumatic throttle idle control
- Honda GX Series OHV Engine or Kohler OHV V-Twin Engine



GT11HGB-B

Single Stage				125 PSI		
Model	Pump	HP	Drive	Pump RPM	CFM Disp	Del'd Air
K5HGA-B	K	5.5	Recoil Start	1285	14.2	8.6
GC8HGA-B	GC	8		890	24.6	16.0
GC11HGA-B		J	11	Electric Start	1070	28.6
J11HGA-B	865				31.8	20.9

Two Stage				175 PSI		
Model	Pump	HP	Drive	Pump RPM	CFM Disp	Del'd Air
GT5HGB-B	GT	5.5	Recoil Start	570	14.2	9.1
GT8HGB-B		8		820	24.6	15.4
GT11HGB-B	W	11	Electric Start	985	28.6	16.3
W11HGB-B				760	24.1	17.6
U18HGB-B	U	18		800	49.8	34.7
T25KGB-B	T	25		625	86.4	67.3

Options

- Oil sight glass
- Air line filter ■ Lubricator
- Electric start
- Other pressures available upon request
- Other engine options available upon request

Electric Stationary Compressors

Standard Features

- Heavy-duty single or two stage cast iron compressor pump
Made in Somerset, PA USA
- Splash lubricated
- Belt driven with a large flywheel for extra cooling and easier start-up
- Each unit is filled with Jenny Ultimate Blue Compressor Pump Oil
- Directional air shroud for reduced pump temperatures
- Totally enclosed heavy-duty belt guard
- Tanks are powder coated and ASME certified
- 60 gallon tanks and larger are ASME National Board certified
- Protectively mounted fittings
- Manual tank drain(s)
- Large canister intake filter with replaceable filter elements
- Special unloading valves to assist in motor starting
- Tank gauge
- Pressure relief safety valve



F13A-17



K15A-30



GC3A-60V



K15A-30V

Single Stage

Model	Pump	HP	Tank Gallon	Power Supply	125 PSI			
					Pump RPM	CFM Disp	Del'd Air	
F12A-17	F	1/2	17	115 Volt (through 2 HP) or 230 Volt 1 Phase	680	3.4	2.2	
F34A-17		3/4			1080	5.3	3.1	
F34A-30		1	560		6.2	4.0		
K1A-30	K	1-1/2	30		870	9.8	6.2	
K15A-30		60			1140	13.1	8.0	
K2A-30		2	30		208, 230, 460 or 575 Volt 3 Phase	480	13.1	9.1
K2A-60			60			770	21.0	14.0
GC2A-30	GC	3	30			1020	27.8	17.8
GC2A-60			60			780	28.7	19.0
GC3A-30		5	30			780	28.7	19.0
GC3A-60			60					
GC5A-60			80					
GC5A-80	J	60						
J5A-60		80						
J5A-80								

Options

- Constant run ■ Dual control ■ Low oil level switch
- Oil sight glass ■ Automatic tank drain
- ASME National Board tank
- Magnetic starter
- Control circuit transformer ■ Vertical tank
- Air line filter ■ Lubricator
- Aftercooler ■ Dryer
- Other pressures available upon request

Electric Stationary Compressors

- Auto Start/Stop control with pressure unloader set at 105-125 PSI (single stage) or 145-175 PSI (two stage)
- Magnetic starter is included on all 5HP and larger units
- Industrial/Commercial grade UL Listed electric motor
- Thermal overload motor protection
- Alternator and magnetic starter are standard on all duplex models



U10B-120

GT5B-80V



T25B-240

W5B-80



Two Stage

Model	Pump	HP	Tank Gallon	Power Supply
GT2B-60	GT	2	60	115 Volt (through 2 HP) or 230 Volt 1 Phase
GT2B-80			80	
GT3B-60			60	
GT3B-80			80	
W3B-60	W	3	60	
W3B-80			80	
GT5B-60	GT	5	60	
GT5B-80			80	
GT5B-120			120	
W5B-60	W	5	60	
W5B-80			80	
W5B-120			120	
U75B-80	U	7-1/2	80	
U75B-120			120	
U10B-80		10	80	
U10B-120			120	
T15B-120	T	15	120	
T15B-240			240	
T20B-120		20	120	
T20B-240			240	
T25B-120			25	120
T25B-240	240			

175 PSI

Pump RPM	CFM Disp	Del'd Air
450	9.1	7.1
660	13.4	10.7
440	12.2	10.7
900	18.3	15.2
760	21.1	17.5
610	38.0	27.2
710	43.6	35.2
520	72.4	56.5
670	92.6	72.2
780	107.0	83.0

Duplex Single Stage

Model	Pump	HP	Tank Gallon	Power Supply
2(K15A)-60	K	3	60	115 Volt (through 2 HP) 230 Volt 1 Phase
2(GC5A)-80	GC	10	80	

125 PSI

Pump RPM	CFM Disp	Del'd Air
870	19.6	12.4
1020	55.6	35.6

Two Stage

Model	Pump	HP	Tank Gallon	Power Supply
2(GT5B)-120	GT	10	120	208, 230, 460 or 575 Volt 3 Phase
2(W5B)-120	W			
2(U10B)-120	U	20	240	208, 230, 460 or 575 Volt 3 Phase Only
2(U10B)-240				
2(T25B)-240				

175 PSI

Pump RPM	CFM Disp	Del'd Air
900	36.6	30.4
762	42.4	35.0
710	87.2	70.4
780	214.0	166.0

Climate Control Compressors

Standard Features

- Heavy-duty cast iron compressor pump
Made in Somerset, PA USA
- Splash lubricated
- Belt driven with a large flywheel for extra cooling and easier start-up
- Each unit is filled with Jenny Ultimate Blue Compressor Pump Oil
- Directional air shroud for reduced pump temperatures
- Totally enclosed heavy-duty belt guard
- Tanks are powder coated and ASME certified
- 60 gallon tanks and larger are ASME National Board certified
- Protectively mounted fittings
- Manual tank drain(s)
- Large canister intake filter with replaceable filter elements
- Special unloading valves to assist in motor starting
- Tank gauge
- Pressure relief safety valve
- Auto Start/Stop control with pressure unloader set at 75-100 PSI
- Magnetic starter is included on all 5HP and larger units
- Industrial/Commercial grade UL Listed electric motor
- Thermal overload motor protection
- Alternator and magnetic starter standard on all duplex models

Simplex Single Stage

Model	Pump	HP	Tank Gallon	Power Supply	Pump RPM	CFM Disp	Del'd Air
F12C-30C	F	1/2	30	See Two Stage	590	2.9	1.7
KC34C-30C	KC	3/4			420	4.8	2.7
K1C-30C	K	1			520	5.9	3.7

Two Stage

Model	Pump	HP	Tank Gallon	Power Supply	Pump RPM	CFM Disp	Del'd Air
GT2C-60C	GT	2	60	115 Volt (through 2 HP) 230 Volt 1 Phase	540	11.0	9.1
W3C-80C	W	3	80		480	13.5	11.6
W5C-80C		5			760	21.5	17.7
U75C-80C	U	7-1/2	80	115 Volt (through 2 HP) 230 Volt 1 Phase	610	38.0	28.5
U10C-80C		10			710	43.6	35.2
T15C-120C	T	15	120	208, 230 460, or 575 Volt 3 Phase	520	72.4	57.5
T20C-120C		20			670	92.6	73.5
T25C-120C		25			780	107.0	85.0

Duplex Single Stage

Model	Pump	HP	Tank Gallon	Power Supply	Pump RPM	CFM Disp	Del'd Air
2(F12C)-30C	F	1	30	115 Volt (through 2 HP) 230 Volt 1 Phase	590	5.8	3.4
2(KC34C)-60C	KC	1-1/2	60		420	9.6	5.4
2(K1C)-60C	K	2	60		520	11.8	7.4

Two Stage

Model	Pump	HP	Tank Gallon	Power Supply	Pump RPM	CFM Disp	Del'd Air
2(GT2C)-60C	GT	4	60	208, 230 460, or 575 Volt 3 Phase	540	22.0	18.2
2(W3C)-80C	W	6	80		480	27.0	23.2
2(W5C)-80C		10			760	43.0	35.4
2(U75C)-120C	U	15	120	115 Volt (through 2 HP) 230 Volt 1 Phase	610	76.0	57.0
2(U10C)-120C		20			710	87.2	70.4
2(T15C)-240C	T	30	240	208, 230, 460 or 575 Volt 3 Phase Only	520	144.8	115.0
2(T20C)-240C		40			670	185.2	147.0
2(T25C)-240C		50			780	214.0	170.0

K1C-30C



W5C-80C



2GT2C-60C

Options

- Low oil level switch ■ Oil sight glass ■ Automatic tank drain
- ASME National Board tank ■ Magnetic starter ■ Control circuit transformer ■ Vertical Tank
- Air line filter ■ Lubricator ■ Aftercooler ■ Dryer

Fire Sprinkler Stationary Compressors

Base Plate Mounted

Standard Features

- Heavy-duty single stage cast iron compressor pump
Made in Somerset, PA USA
- Splash lubricated
- Belt driven with a large flywheel for extra cooling and easier start-up
- Each unit is filled with Jenny Ultimate Blue Compressor Pump Oil

- Directional air shroud for reduced pump temperatures
- Totally enclosed heavy-duty belt guard
- Powder coated, extra heavy steel base plate
- Large canister intake filter with replaceable filter elements
- Magnetic starter is included on all 5HP and larger units
- Industrial/Commercial grade UL Listed electric motor
- Thermal overload motor protection



Base Mounted System Size

Maximum Gallons in system to be pumped to 40 PSI in 30 Minutes

Model	Pump	HP	Power Supply	Pump RPM	CFM del'd @ 40 PSI	Optional Auto Control Group		
220	F13S-BS	1/3	115 Volt (through 2 HP) or 230 Volt 1 Phase	670	2.9	ACGF		
290	F12S-BS	1/2		950	3.8			
350	F34S-BS	3/4		1200	4.4			
425	K34S-BS			520	5.3	ACGK		
480	F1S-BS	F		208, 230, 460 or 575 Volt 3 Phase	1430	6.0	ACGF	
600	K1S-BS	K			790	7.4	ACGK	
885	K15S-BS				1-1/2	1140		10.9
985	K2S-BS	G			1280	12.4	ACGD	
1215	G2S-BS				2	630		15.1
1775	G3S-BS				3	950		21.8
1950	GC5S-BS	J		5	1030	24.2	ACGJ	
2115	J5S-BS				830	26.0		

Tank Mounted/30 Gallon

Model	Pump	HP	Power Supply	Pump RPM	CFM del'd @ 40 PSI	Optional Auto Control Group		
220	F13S-30UMS	1/3	115 Volt (through 2 HP) 230 Volt 1 Phase	670	2.9	ACGF		
290	F12S-30UMS	1/2		950	3.8			
350	F34S-30UMS	3/4		1200	4.4			
425	K34S-30UMS			520	5.3	ACGK		
480	F1S-30UMS	F		208, 230, 460 or 575 Volt 3 Phase	1430	6.0	ACGF	
600	K1S-30UMS	K			790	7.4	ACGK	
885	K15S-30UMS				1-1/2	1140		10.9
985	K2S-30UMS	G			1280	12.4	ACGD	
1215	G2S-30UMS				2	630		15.1
1775	G3S-30UMS				3	950		21.8
1950	GC5S-30UMS	J		5	1030	24.2	ACGJ	
2115	J5S-30UMS				830	26.0		

Tank Mounted

Additional Standard Features

- Tanks are powder coated and ASME certified
- Protectively mounted fittings
- Manual tank drain(s)
- Large canister intake filter with replaceable filter elements
- Special unloading valves to assist in motor starting
- Tank gauge
- Pressure relief safety valve
- Auto Start/Stop control with pressure unloader set at 25-40 PSI

Options

- ASME National Board tank
- Magnetic starter
- 17 gallon tank
- Vertical tank
- Low oil level switch
- Oil sight glass
- Automatic tank drain
- Air line filter
- Aftercooler
- Dryer
- Control Group



F12S-30S



GC5S-30S



K15S-30S



AIR COMPRESSORS Jenny®

Jenny Products, Inc.
850 North Pleasant Avenue
Somerset, PA 15501-1069
Phone 814-445-3400
Fax 814-445-2280
www.jennyproductsinc.com

.438 DIA
HOLE

1/2" NPT WELD
FLANGING

Ø 25.00