## Single Stage Wheeled Portable

## **Standard Features**

- Heavy-duty single stage cast iron compressor pump
  Made in Somerset, PA USA
- Splash lubricated
- Belt driven with a large flywheel for extra cooling and easier start-up
- Each unit is filled with Jenny Synthetic Blue Compressor Pump Oil
- Directional air shroud for reduced pump temperatures
- Totally enclosed heavy-duty belt guard
- 8 & 15 gallon tanks are low profile, powder coated twin tank receivers
- 17 and 30 gallon tanks are powder coated and ASME certified
- Convenient lifting handles
- Anti-vibration feet
- Pneumatic tire(s)
- Protectively mounted fittings
- Manual tank drain(s)
- Large canister intake filter with replaceable filter elements
- Special unloading valves to assist in motor starting
- Stainless steel braided discharge hose
- Tank gauge
- Regulator and outlet pressure gauge
- Pressure relief safety valve
- Designed, tested and proven to meet the demands of the construction and rental industry





## **Electric Motor**

- Constant run control set at 105-125 PSI
- High quality pilot valve
- Industrial/Commercial grade UL Listed electric motor
- Thermal overload motor protection
- 6 ft power cord





				Tank	Power	CFM@	CFM@
	Model	Pump	HP	Gallon	Supply	100 PSI	125 PSI
	K1A-8P	K	1	8	115 or 230 Volt 1 Phase	4.2	4.0
_	K1A-15P			15			
	K1A-17P			17			
	K1A-30P			30			
	K15A-8P		1.5	8		6.5	6.2
	K15A-15P			15			
	K15A-17P			17			
	K1A-30P			30			
	K2A-8P		2	8		8.4	8.0
_	K2A-15P			15			
	K2A-17P			17			
	K2A-30P			30			
_	G3A-8P	G	3	8	230 Volt 1 Phase	13.8	13.5
	G3A-15P			15			
	G3A-17P			17			
	G3A-30P			30			
	G5A-8P		5	8		18.3	17.8
	G5A-15P			15			
	G5A-17P			17			
	G5A-30P			30			
	J5A-30P			30		19.4	19.0

## **Options**

Start-Stop control ■ Dual control

Dual voltage switch ■ On-Off switch

Two wheel option (8 & 15 gallon models)

CSA option ■ Oil sight glass ■ Air line filter ■ Lubricator

Other pressures available upon request