

Electric Stationary Compressors

- Auto Start/Stop control with pressure unloader set at 105-125 PSI (single stage) or 145-175 PSI (two stage)
- Magnetic starter is included on all 5HP and larger units
- Industrial/Commercial grade UL Listed electric motor
- Thermal overload motor protection
- Alternator and magnetic starter are standard on all duplex models



U10B-120

GT5B-80V



T25B-240



W5B-80

Two Stage

Model	Pump	HP	Tank Gallon	Power Supply	175 PSI Pump RPM	CFM Disp	Del'd Air				
GT2B-60	GT	2	60	115 Volt (through 2 HP) or 230 Volt 1 Phase	450	9.1	7.1				
GT2B-80			80		660	13.4	10.7				
GT3B-60			W		3	60	440	12.2	10.7		
GT3B-80						80	900	18.3	15.2		
W3B-60	GT	5	60		208, 230, 460 or 575 Volt 3 Phase	760	21.1	17.5			
W3B-80			80								
GT5B-60			60								
GT5B-80	U	7-1/2	80			610	38.0	27.2			
GT5B-120			120								
W5B-60	W	10	60			710	43.6	35.2			
W5B-80			80								
W5B-120	T	15	120			208, 230, 460 or 575 Volt 3 Phase Only	520	72.4	56.5		
U75B-80			U							20	80
U75B-120											120
U10B-80			T	25						80	670
U10B-120	120										
T15B-120	T	25	120	780			107.0	83.0			
T15B-240			240								
T20B-120			120								
T20B-240			240								
T25B-120	T	50	120	780	214.0	166.0					
T25B-240			240								

Duplex Single Stage

Model	Pump	HP	Tank Gallon	Power Supply	125 PSI Pump RPM	CFM Disp	Del'd Air
2(K15A)-60	K	3	60	115 Volt (through 2 HP) 230 Volt 1 Phase	870	19.6	12.4
2(GC5A)-80	GC	10	80		1020	55.6	35.6

Two Stage

Model	Pump	HP	Tank Gallon	Power Supply	175 PSI Pump RPM	CFM Disp	Del'd Air
2(GT5B)-120	GT	10	120	208, 230, 460 or 575 Volt 3 Phase	900	36.6	30.4
2(W5B)-120	W				762	42.4	35.0
2(U10B)-120	U	20	240	208, 230, 460 or 575 Volt 3 Phase Only	710	87.2	70.4
2(U10B)-240					T	50	780